

Introducing the Toccare All-In-One D510

Toccare Touch Screen and Integrated Touch PoS

Designed for all-in-one touch application and other high-standard industries.



Features

- Bezel free design and glass finish screen.
- Perfect picture clarity through high light transmission.
- High durability and anti contamination for heavy workload and harsh application.
- Utilise multi-touch technology and create innovative applications to enhance the customer experience.
- Combines style with full functionality.
- Integrated in one system, with small footprint for space saving.
- Designed with Intel® Atom processor D510, 1.6GHz, FSB 533 MHz.
- Compact size and elegant design, with all cables well-protected and managed in system.
- Lockable OSD buttons to provide security.
- Optional 3 track MSR available.



Introducing the Toccare All-In-One D510

Specifications

MODEL	Toccare D510 15" (high gloss only) and 22" Bezel Free
DIMENSIONS (INCL STAND)	364.43 (W) X 322.12 (H) X 206.21 (D) mm (15" version)
WEIGHT (NET / SHIPPING)	6.04 kg / 8.93 kg (approx.)
MOUNTING OPTION	Stand / 75 x 75 mm VESA Mount
CPU	Intel © Atom Processor D510, 1.6GHz, FSB 533 MHz
CHIPSET	Mobile Intel © ICH8M Express
BIOS	Intel © BIOS
VGA PORT	Intel © GMA3150 Onboard Graphics
MEMORY	DDR II 533 SODIMM Socket x 1 (up to 4GB)
LAN	RJ45 (10/100/1000)
USB	4 X USB 2.0, 2 X 12V PUSB, 1 X 24V PUSB
I/O CONNECTORS	1 X Powered RS232 1 X VGA (2 nd Video Out) 1 X CD Port RJ11
LCD SIZE / TYPE	15" (high gloss only) or 22" Diagonal TFT Active Matrix Panel
PANEL RESOLUTION	1024 X 768 (Max.)
DISPLAY COLOUR	16.7M (6 bits + FRC)
RESPONSE TIME	8ms (typical)
VIEWING ANGLE	Horizontal: 140° (typical) Vertical: 125° (typical)
VIDEO SIGNAL OUTPUT	VGA
HDD STORAGE	SSD (mS-ATA)
AUDIO	Realtek HD Audio
PERIPHERALS	3 Track MSR (Optional)
TOUCH TECHNOLOGY	Projected Capacitive Touch
TOUCH INTERFACE	USB
COMPLIANCE	TUV, CE, UL, CUL, FCC-B, RoHS, IPS4

DigiPoS Store Solutions North America

